

Cascade

# PAP200LP

200 mm Semi-automatic Pressure Probe System

000111100010

## Overview


Cascade PAP200LP from FormFactor probe system from FormFactor is the ideal probing solution for testing MEMS pressure sensors with high accuracy at above/below atmospheric air pressure. The entire 200 mm probe is integrated into a pressure chamber rated from 500 mbar to 1200 mbar absolute.

To meet the production test requirements, the PAP200LP is equipped with a high-speed 200 mm chuck stage, designed for use with standard 4.5" probe cards. The modular design of the PAP200LP enables a wide range of measurements, including I-V for piezo-resistive and C-V for capacitive pressure sensors.

The PAP200LP is equipped with a stable vibration isolating frame. The pressure chamber with topside viewport and an optical window made of quartz glass contains flanges for vacuum-tight electrical feedthroughs. The pressure control system consists of a powerful diaphragm vacuum pump, a remote controlled proportional valve for air dosage and a high-precision pressure sensor to monitor the environmental conditions.

All main functions, i.e. stage movement and pressure control, can be controlled by software. The large front door allows quick and ergonomic loading and unloading of the wafer, as well as easy probe card exchange. A swivel mechanism, which is part of the microscope station, allows convenient access to the topside lid.

The PAP200LP can be customized with a variety of instrumentation, such as video microscopes, laser cutters and Polytec's optical motion analysis tools. Specially designed thermal chucks, with electrical and coolant bulk feed throughs, are available for the use under vacuum conditions. The PAP200LP supports a wide temperature range from -60°C to 200°C, and a dew point sensor ensures condensation-free probing.



## Features / Benefits

<b>High throughput</b>	<ul style="list-style-type: none"><li>• Patented wafer-exchange mechanism for quick loading / unloading</li><li>• High-speed stage with up to five dies/s without compromising accuracy</li></ul>
<b>High accuracy</b>	<ul style="list-style-type: none"><li>• Special pressure control system with <math>\pm 0.05</math> % accuracy</li></ul>
<b>Ease of use</b>	<ul style="list-style-type: none"><li>• Large front door for easy probe card exchange</li><li>• All main functions controlled by software</li></ul>
<b>Flexibility</b>	<ul style="list-style-type: none"><li>• Several flanges for flexible configuration</li><li>• Electronics rack providing space for test instruments</li></ul>

## > Specifications\*

### Chuck Stage

<b>X-Y Movement</b>	<b>Closed-loop DC servo with linear encoder feedback</b>
Travel	205 mm x 205 mm
Resolution	1.0 $\mu\text{m}$
Repeatability	$\pm 2.0 \mu\text{m}$
Accuracy	$\pm 5.0 \mu\text{m}$

<b>Z Movement</b>	<b>DC servo with linear encoder feedback</b>
Travel	15 mm
Resolution	0.25 $\mu\text{m}$
Repeatability	$\pm 1.0 \mu\text{m}$

<b>Theta Movement</b>	<b>DC servo with linear encoder feedback</b>
Travel	$\pm 6.0^\circ$
Resolution	0.0001 $^\circ$

<b>Pressure Supply System</b>	
Range	500 to 1200 mbar absolute (other on request)
Accuracy	$\pm 0.05 \%$ of full range ( $\pm 0.025$ on request)

<b>Electrical Data</b>	
System power (internal)	230 V, 50/60 Hz, 3800 VA

<b>Utilities Required</b>	
Compressed air input	0.5 MPa to 0.6 MPa or 5 bar to 6 bar; hose of 8 mm outer diameter
N2 input	Class 4.6 or better; 4 bar; 8 mm outer diameter tube
Exhaust	50 mm hose

<b>Microscope</b>	
Type	Fits to video and stereo microscopes

<b>Probe Platen</b>	
Type	4.5" probe card adapter

<b>Chucks</b>	
Standard	150 mm or 200 mm; stainless steel
Thermal	200 mm; -60°C to 200°C

\* Data, design and specification depend on individual process conditions and can vary according to equipment configurations. Not all specifications may be valid simultaneously.

## Physical Dimensions


### Dimensions (WxDxH)

Probe station	1100 mm x 1100 mm x 1500 mm
Rack	600 mm x 800 mm x 1000 mm


### Weight

Chamber unit with frame work	400 kg
Vibration isolating table	150 kg
Rack	50 kg


## Applications



Probe station with electronic rack and thermal chuck controller.



Pressure Control Software.



© Copyright 2018 FormFactor, Inc. All rights reserved.  
FormFactor and the FormFactor logo are trademarks of  
FormFactor, Inc. All other trademarks are the property of  
their respective owners.

All information is subject to change without notice.

**Corporate Headquarters**  
7005 Southfront Road  
Livermore, CA 94551  
Phone: 925-290-4000  
www.formfactor.com

PAP200LP-DS-0418